



I M P O R T A N T :

The controller operating temperature of the Microsemi Adaptec® Series 2/2Q, 5/5Q, 6/6E/6T/6H, 7/7Q/7H, and 8/8Q/8E is 0°C–55°C*, 200LFM. For the Microsemi Adaptec Series 5/5Q with battery backup, it is 0°C–40°C*, 200LFM; for the Microsemi Adaptec Series 5Z/5ZQ and Series 6Q/6TQ, it is 0°C–50°C*, 200LFM. For the Microsemi Adaptec Series 7/7Q and Series 8/8Q/8Z/8ZQ with flash backup, it is 0°C–55°C*, 200LFM. For the Microsemi Adaptec SAS Expander AEC-82885T, it is 0°C–55°C*, 200LFM.

It is essential to provide sufficient airflow to the RAID processor with the controller installed in a server or PC chassis. A minimum airflow of 200LFM (linear feet per minute) or higher is required for proper functionality.

<http://ask.adaptec.com/thermal>

* **Note:** Ambient temperature measured 1 inch (2.54 cm) away from the RAID processor.

N O T E :

Please observe best practices for RAID controller board installation. For example, all drive cabling should be secured to the chassis to prevent the cables from causing the controller to flex or unseat if the chassis experiences shock.

© 2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation.

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense and security, aerospace, and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs, and ASICs; power management products; timing and synchronization devices and precise time solutions; voice processing devices; RF solutions; discrete components; enterprise storage and communications solutions; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees world-wide. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

The technology discussed in this document may be protected by one or more patent grants.

Part Number: MAN-00258-01-A Rev J